




BUEHLER

IsoMet™ High Speed Precision Cutter

IsoMet™ High Speed and High Speed Pro






IsoMet High Speed Features

The IsoMet High Speed is a versatile table top precision saw that provides efficient and precise cuts for any application. The innovative machine and vise designs make setup quick and simple by using the precision laser. Align cuts quickly by using three axis blade movement, and tool-less vising adjustment. Optimize cut quality through out the blade life with the automatic dressing system.



Precision cutting is vital for thermal spray coatings analysis. The diamond blade minimizes the damage to a cut surface for analysis.




A challenge of micro-sectioning is to create a planar surface at a specified location. Precision alignment to an accuracy of one micron is crucial for analysis.



Specialized materials are valuable and minimizing scrap is important. Confidence in sectioning equipment to perform the same process every time.


EFFICIENT
CONSISTENT
PRECISE



Efficient


Save Time

The IsoMet High Speed has a blade motor power of 2kW, which is the strongest motor on the market. This motor power ensures the blade will minimize the deformation of the sample surface, saving you time later in the material preparation process. Reduce the cut time without impacting the surface quality. In a side by side comparison, the IsoMet High Speed cut over 2.5X faster than a leading competitor with the same or better cut quality.



These real time results were collected by a leading Aerospace company.






Minimize Setup




Buehler's Rapid Rail System allows users to secure samples in the cutting chamber and begin the next cut within seconds.

Easy to Use


The IsoMet High Speed has a variety of programmable capabilities. The simple user interface keeps the most important and frequently used features within one touch from the home screen.



Available in 10 different languages




The new vise system has reduced the need for tools and allows for rapid changing of samples and sample types with the same vise.



Consistent

Smart Cut

SmartCut™ adjusts the cut speed in real time to ensure the cut quality is not compromised while maintaining the efficiency of a powerful cut.



From the Home screen, Press the "Smart Cut" button.




Watch the "Motor" icon adjust to optimize the cut





Repeatable Cut

Improve consistency with saved methods that load preprogrammed parameters from the home screen. Methods remove the need to remember cut parameters.



From the Home screen, either save or recall methods by pressing the "Saved Method" or "Method" button.



Precise

Alignment


The machine has an accuracy of one micron in the X direction. The precision of the machine is all in the blade movement reducing the potential to revise and manually move samples.

Serial Sectioning


With precise X movement of the blade, make multiple cuts on one sample all within one programmed cut. For the versatile lab, cut location can either be uniformly or placed individually.

High Quality Cut

Consistent cuts are vital to sample analysis. The IsoMet High Speed allows features to be locked on the machine to ensure the same parameters are used every time. Program the automatic dressing system to maintain consistent cut quality and extend diamond blade life. Reduce the frequency of changing the dressing stick with the new optimized dressing wheel design.




From the Home screen, press the "Menu" button.



From the Menu screen, press the "Lock" button.










This screen allows for multiple features of the machine to be locked during standard operation.





Match Versatility with the IsoMet High Speed

The IsoMet High Speed is a quality machine with the focus on efficiency, consistency, and precision. The IsoMet High Speed Pro has all the benefits of the IsoMet High Speed with added features to enhance the user experience.

	IsoMet High Speed Pro	IsoMet High Speed
 Smart Cut Automatically optimize cuts	●	●
 Serial Cut Cut multiple samples in one program	●	●
 Passcode Lock Selectively lock out machine settings	●	●
 Saved Methods Save programmed cut parameters	●	
 Automatic Dressing System Dress blades automatically during cuts	●	
 Z Axis Movement Adjust cut location for optimization	●	
 Green Laser Easy alignment of cut on sample	●	

Cut Capacity

The IsoMet High Speed has the benefits of precision with the versatility of sample size. To achieve optimal cut capacity, creative vising is required.



Technical Specifications

IsoMet High Speed

IsoMet High Speed Pro

Operation

Cut Operation	Automatic, Manual, or Smart Cut control Linear Blade Feed	
Units	English and Metric	
Blade Movement Axis	Horizontal and Linear (X, Y)	Horizontal, Linear, Vertical (X, Y, Z)
Display	6.5in LCD Display with LED Back lighting	
Controls	Touch Screen; Precision Controllers;	
Lighting	2 LED Strip, Adjustable brightness	
Programming	Retains Last Settings Serial Sectioning	Retains Last Settings Customizable Methods Serial Sectioning
Laser	Green Laser	

Dimensions

Blade Position Settings	Horizontal: 0 - 2in [0 - 50mm]	Horizontal: 0 - 2in [0 - 50mm] Vertical: 0 -2in [0 - 50mm]
Cut Length Range	0.01 - 7.25 in [1mm - 184mm]	
Cut Length Increment	0.01 in [1mm]	
Feed Rate Range	0.04 - 1 in/min [1 - 25mm/min]	
Feed Rate Increment	0.01in increments [1mm increments]	
Blade Speed	1000-5000rpm	
Cut Capacity Diameter	2.8in [71mm]	
Coolant Systems	Built-in Recirculating System, 1gal [4L]	
Flow Rate Wash Down Hose	2L/min	
Flow Rate on Blade	2.5L/min	
Wafering Blade Diameters	3 - 8in [76-203mm]	
Abrasive Blade Diameters	5 - 8in [127 - 200mm]	
Cut Chamber Size	9in x 20in [228mm x 508mm]	
Machine Dimensions	Width: 24in [610mm] Depth: 30in [762mm] Height (Hood Opened): 36in [915mm] Height (Hood Closed): 19in [483mm]	
Weight	157Lbs [71.2kg]	


Electrical

Motor Power at 220VAC	2.68Hp [2kW]
Main Power	100 - 240VAC, 50-60Hz, 1 Phase
Noise Level	58dB
Safety Features	Interlock Hood Switch, Emergency Stop
Compliance	CE Directives

Ordering Information

Get Started

Choose the IsoMet High Speed model to best fit lab needs.



IsoMet High Speed (11-2600)


Includes:

Rapid Rails, Rapid Rail Vise Holder and Single Saddle Chuck

Rapid Rail Vise Holder



Single Saddle Chuck



IsoMet High Speed Pro (11-2700)

Includes:

Rapid Rails, Rapid Rail Vise Holder, Single Saddle Chuck and Dressing Wheel.


Rapid Rail Vise Holder



Single Saddle Chuck



Dressing Wheel



Required Accessories

Visit www.buehler.com to select application specific blades and flanges.



Precision Blades

Range in sizes from 3in[76mm] to 8in[203mm]


-or-

Abrasive Blades

Range in sizes from 5in[127mm] to 7.87in[200mm]



Flange Sets



Range in sizes from 3in[76mm] to 6in[152mm]

Cooling Fluid



Water miscible fluid concentrate


Optional Accessories

External Recirculating System Kit (11-2640)



Increases cutting fluid capacity to 7gal [26.5L] at 1.25gal/min [4.7L/min]

Dressing Wheel



Part Number:

11-2655 20 HC, 15HC, 20LC, 15LC, CBN HC, and CBN LC blades
11-2656 10 LC and 5LC blades




Additional Vising Options

The IsoMet comes with the Rapid Rails installed.


Rapid Rail Vise Holder (11-2660)

Increase productivity with additional rapid rail holders




Large, Single Saddle Chuck (11-2661)

Holds specimens up to 1.5in [38mm] from 2 point



Double Saddle Chuck (11-2662)

Securely holds specimens up to 1.5in [38mm] from 2 points



Quick Clamp Vise


Stainless steel chuck holds mounted samples



Part Number:
 11-2666 1.25in[30mm]
 11-2667 1.5in[40mm]

Fastener Chuck (11-2687)

Holds specimens up to 2in [50mm] for longitudinal sectioning




Large Bone Chuck (11-2494)

Ideal for clamping bone, plastics, or other semi-rigid specimens up to 2in [50mm] in diameter




Irregular Specimen Chuck (11-1185)

Adjusts to hold irregular shaped specimens up to 1in [25mm] in diameter



T-slot bed (11-2707)

Add a T-Slot bed to the machine for additional vising options




Small Speed Vise (460022)

Clamps specimens up to 58mm in height




Sliding Vise (11-2669)

6in [152mm] maximum opening, use requires flange to be 2in [50mm] or less




Vee Blocks Clamp Kit (10-3527)

Raise samples above the table



Buehler Worldwide Locations



Solutions for Materials Preparation, Testing and Analysis

BUEHLER

41 Waukegan Road, Lake Bluff, Illinois 60044
P: 847 295 6500 | 800 BUEHLER (800 283 4537)
W: www.buehler.com | **E:** info@buehler.com

North America-South America Offices

BUEHLER Worldwide Headquarters
P: 847 295 6500 | 800 BUEHLER (800 283 4537)
W: www.buehler.com | **E:** info@buehler.com

Europe Offices

BUEHLER Germany - Esslingen
European Headquarters
P: +49 (0) 711 4904690-0
E: info.eu@buehler.com

BUEHLER France - Dardilly
P: +33 (0) 800 89 73 71
E: info.eu@buehler.com

BUEHLER United Kingdom - Coventry
P: +44 (0) 800 707 6273
E: info.eu@buehler.com

Asia-Pacific Offices

BUEHLER Japan
P: +81 03 5439 5077 | **F:** +81 03 3452 7220
E: info.japan@buehler.com

BUEHLER Asia-Pacific - Hong Kong
P: +852 2307 0909 | **F:** +852 22721 6659
E: info.asia@buehler.com

BUEHLER China - Shanghai
ITW Test & Measurement (Shanghai) Co., Ltd.
P: +86 400 000 3418 | **F:** +86 21 6410 6671
E: info.cn@buehler.com

Visit www.buehler.com for more information on a Buehler location near you.

